

WLED DC BATTERY BACKUP BELT DRIVE LED WI-FI® GARAGE DOOR OPENER

Corner to Corner Lighting™ makes the entire garage bright.



KEY FEATURES

ULTRA-BRIGHT

Lighting

QUIET

Operation

POWER-OUTAGE

Performance

WI-FI

Built In

BATTERY BACKUP
CALIFORNIA SB-969
COMPLIANT



myQ integrates with leading smart home platforms. Visit myQ.com to learn more.

SECURE

CORNER TO CORNER LIGHTING WITH LONG-LASTING LEDS DELIVERS 3,100 LUMENS OF DAYLIGHT-LIKE LIGHTING TO THE ENTIRE GARAGE SPACE.

AUTOMATIC GARAGE DOOR LOCK CAPABLE: DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

TIMER-TO-CLOSE CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

SECURITY+ 2.0® SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

QUIET AND RELIABLE

BELT DRIVE SYSTEM AND QUIET DC MOTOR PROVIDE SMOOTH OPERATION AND LONG-LASTING SERVICE.

SOFT START/STOP FOR SMOOTH OPERATION.

BATTERY BACKUP ENSURES GARAGE ACCESS EVEN WHEN THE POWER'S OUT.

WARRANTY LIFETIME MOTOR, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

myQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

*Linking your myQ account to a partner may require an additional accessory purchase or subscription fee. Smartphone not included.

INCLUDED ACCESSORIES:

SMART CONTROL PANEL®

LCD display enables simple programming and adjustment of settings.



880LMW

3-BUTTON REMOTE CONTROL

Operates up to 3 openers or myQ Light Accessories.



893MAX

INTEGRATED BATTERY BACKUP

Powers up the opener when the power's out.



485LM

POWERFUL ADD-ONS:

AUTOMATIC GARAGE DOOR LOCK CAPABLE

Deadbolts the garage door automatically every time it closes.



841LM

myQ HOME BRIDGE

Adds Apple® HomeKit™ compatibility and Siri® voice control to Wi-Fi-enabled openers. Installs easily in the garage within Wi-Fi range.**



819LMB

REMOTE LIGHT CONTROL

Plug in any lamp to this device to control it with a smartphone or garage remote.



825LM

MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



374UT

WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



877MAX

PRODUCT GUIDE WLED

DC BATTERY BACKUP BELT DRIVE
LED WI-FI GARAGE DOOR OPENER

LiftMaster®

WLEDDC BATTERY BACKUP BELT DRIVE
LED WI-FI® GARAGE DOOR OPENER

MASTERFUL ENGINEERING.

MOTOR



- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER



- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 6' Power Cord (3-Prong)

MECHANICS



- **Steel Chassis, T-Rail and Trolley**
- **Full Reinforced Belt Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- **2 Lock Terminals** Allow up to 2 Locks to Be Connected (Sold Separately)

7.5"



DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

9"

Per second for door to move upward

SPEED

6.5"

Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -40°F to 150°F

3-Button Remote Control (893MAX)

- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Smart Control Panel® (880LMW)

- Timer-to-Close
- Program Remote Controls, Keypads and myQ Accessories
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

myQ® RADIO



- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER**)

**May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- 2 LED Light Panels
- 100 Points of LED Light
- 3,100 Lumens,*** 4,000 Kelvin Light Temperature
- Adjustable Time
- Disabled in Battery Backup Mode

***Verified by an independent lab.

SHIPPING.

SHIPPING WEIGHT (in lbs.)



HEAD



RAIL



AUTOMATIC GARAGE DOOR LOCK (OPTIONAL)

CARTONS (3)

CARTON 1: 19.81" x 11.94" x 11.19"

- Garage Door Opener Head (WLED) with Integrated Battery Backup (485LM)
- Smart Control Panel (880LMW)
- 3-Button Remote Control (893MAX)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Belt T-Rail

CARTON 3 (OPTIONAL): 8" x 4.5" x 4"

- Automatic Garage Door Lock (841LM)

SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert 2-Close/Unattended Close Operation†
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 myQ Devices



†WARNING: to reduce the risk of injury to persons—ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.